


THERMOCOUPLE WITH NIPPLE & STRAIGHT T/W

T-652



Thermocouple Element

Termination Style

Junction Style

Sheath "OD"

Sheath Material

Thermowell Material

Thermowell OD X ID :

Nipple

Length of "T"

Process Connection

Inst. Connection

Insertion Length (I.L.)

Extention Length (E.L.)

Nominal Length of T/C "L"

Type of T/C	Description
K	Chromal/Alumal
J	Iron/Constantan
N	Nicrosil-Nisil
T	Copper/Constantan
E	Ni-Cr/Constantan
Other	Consult Factory
Ex. :	If Simplex - K Duplex - KK

C	Connection Head IP-67
M	Miniature Head
D	Double entry Head IP-65
E	Ex. Proof Head-IIA/IIB
P	Plastic Head
Other	Consult Factory

GN	Grounded Rounded Tip
UN	Ungrounded Rounded Tip

1	Ø1mm
1.6	Ø1.6mm
3	Ø3mm
4.5	Ø4.5mm
6	Ø6mm
8	Ø8mm

316	SS 316
310	SS 310
304	SS 304
600	Inconel-600
800	Inconel-800
446	HRS-446
Other	Consult Factory

A	1/2" SCH 80
B	1/2" SCH 40
Other	Consult Factory

Threads	1/4"
	1/2"
	3/4"
	3/8"
	1"
B.S.P. / N.P.T.	1 1/4"
	1 1/2"
	2"
M-Thread	M20X1.5, M18X1.5, M33X2
Other	Consult Factory